






GREENCO




G-2RB

Performance curve for Vacuum pump



2RB 230

Performance curve for Compressor



The performance curves are based on air at a temperature of 15 °C and an atmospheric pressure of 1013 mbar with a tolerance of +/- 10 %.
The total pressure differences are valid for suction and ambient temperatures up to 25 °C.
For other conditions please confer with us.

Each G-2RB type can be applied both as vacuum pump and compressor in continuous operation over the total stated performance curve range. The motors are available as standard for the input voltage range of 50 and 60 Hz and for protection category IP 55 as well as approved for UL and CSA.

Selection and ordering data

Type 2RB230

Curve No.	Order No.	Frequency Hz	Rated power kW	Input voltage V		Input current A		Permissible total differential pressure ²⁾		Sound pressure level ³⁾ dB(A)	Weight ca. kg
				Vacuum mbar	Compressor mbar						

3~ 50/60 Hz IP55 insulation material class F 1)

A 150	2RB230-7AH06	50	0.25	200D ... 240D	345Y...415Y	2.1D	1.2Y	-80	80	54	10
A 151	2RB230-7AH06	60	0.29	220D ... 275D	380Y...480Y	1.7D	1.0Y	-80	80	57	10
A 152	2RB230-7AH16	50	0.4	200D ... 240D	345Y...415Y	2.6D	1.5Y	-120	130	54	11
A 153	2RB230-7AH16	60	0.5	220D ... 275D	380Y...480Y	2.6D	1.5Y	-150	155	57	11
A 154	2RB230-7AH26	50	0.7	200D ... 240D	345Y...415Y	3.8D	2.2Y	-120	130	54	12
A 155	2RB230-7AH26	60	0.83	220D ... 275D	380Y...480Y	3.8D	2.2Y	-165	180	57	12

1~ 50/60 Hz IP55 with attached condenser for continuous operation

A 152s	2RB230-7AA11	50	0.37	230		2.7		-110	110	54	11
A 153s	2RB230-7AA11	60	0.45	230		3.0		-130	140	57	11
A 154s	2RB230-7AV15	50	0.37	115	230	5.4	2.7	-110	110	54	11
A 155s	2RB230-7AV15	60	0.45	115	230	6.0	3.0	-130	140	57	11



Other voltage ranges

2RB230-7AH □.□

50Hz	60Hz	↑	↑
------	------	---	---

3~

185...225 V D/320...390 V Y	200...240 V D/345...415 V Y	H 1
200...240 V D/345...415 V Y	200...275 V D/380...480 V Y	H 6
345...415 V D	380...480 V D	H 7
500 V D	575VD	C 5

Machines according to the ATEX norm 94/4 EG are available for the whole performance range.

Following types available: Category 3 G, 3/2 G, 3 D and 3/2 D.

1~

100 / 200 V	100 / 200 V	V 4
115 / 230 V	115 / 230 V	V 5
230V	---	A 1

Further voltage range on request; please quote in plain text.

All G-2RB achieve the standards and norms of the low voltage directive (LVD)2006/95/EC, rotating electrotechnical motor EN 60034-1-2004, electromagnetic compatibility(EMC)EN55014-1/2,EN61000-2/-3/-4/-6.

- 1) For standard UL for ELECTRIC MOTOR UL 1004-1.
- 2) Relief-valve are available for limiting differential pressure.
- 3) Measuring-surface sound-pressure level acc. to DIN EN 21680, measured at a distance of 1 m. The pump is throttled to an average suction pressure, a hose is connected to the discharge side (compressor) / suction side (vacuum pump), but is not fitted with relief valves.

The motors are designed according to the DIN EN 60 034 / DIN IEC 34-1 and temperature class F.

For the three phase machines the tolerances are +/- 10 % for fixed voltage and +/- 5 % for voltage range.

The single phase machines are designed with a +/- 5 % tolerances. If only 90 % of the maximum allowed pressure will be used for the continuous operating then the allowed voltage range add to +/- 10 %.

For all single and three phase machines which designed according to the UL and CSA norm (UL 1004-1) the maximum allowed voltage tolerances are - 10 % resp. + 6 %.

The frequency tolerance is maximum +/- 2 %.

Changes in particular the quoted performance curve, data and weights without prior notice. The figures are without obligations.